

# **API 7K, 16C and 16D Hose**



## **Feature**

- ✓ All Kelly Rotary Hoses are API 7 K Tested, Certified and monogrammed
- ✓ All Choke and Kill Hoses are API 16C Tested, Certified and monogrammed,
  SS armored and fire retarded
- ✓ Design temp -45 C to 121 C( -49F to 250F)
- ✓ FSL 2 & 3 For all Kelly hose and Choke and Kill hoses.
- ✓ Suitable for oil based muds
- ✓ Meets up to 5-10% H2S Content( HNBR and Stainless steel material )

# **Products**

- API7K Certified High-Pressure Rotary Drilling Hose
- API 16C Stainless Steel Armored Flexible Choke & Kill Hose
- API 16C CR Rubber Armored Flexible Choke & Kill Hose
- API 16D BOP Accumulator Control Hose

#### Hose construction



- 1 Inner Tube: HNBR
- 2 Fiber line Layers
- 3 Middle Rubber Layers
- 4 Steel Wire Reinforcement Layers
- Fire-Resistance Rubber Layer
- S.S Armored Layer

## 9. Hose construction



- 1 Inner Tube: Black NBR
- Fiber line Layers
- 3 Middle Rubber Layers
- 4 Steel Wire Reinforcement Layers
- Fire-Resistance Rubber Laver
- 6 Green Flame Retardent CR Rubber, Over Rubber Layer NR+CR+SBR of Heat Resistance Fiber.











----- Service Count-----Performance Matter, Service Count-----