

API 7K, 16C and 16D Hose



Feature

- ✓ All Kelly Rotary Hoses are API 7 K Tested, Certified and monogrammed
- All Choke and Kill Hoses are API 16C Tested, Certified and monogrammed,
 SS armored and fire retarded
- ✓ Design temp -45 C to 121 C(-49F to 250F)
- ✓ FSL 2 For all Kelly hose and Choke and Kill hoses.
- ✓ Suitable for oil based muds
- ✓ Meets up to 5-10% H2S Content(HNBR and Stainless steel material)

Products

- API7K Certified High-Pressure Rotary Drilling Hose
- API 16C Stainless Steel Armored Flexible Choke & Kill Hose
- API 16C CR Rubber Armored Flexible Choke & Kill Hose
- API 16C BOP Accumulator Control Hose

Hose construction



- 1 Inner Tube: HNBR
- 2 Fiber line Layers
- 3 Middle Rubber Layers
- 4 Steel Wire Reinforcement Layers
- 5 Fire-Resistance Rubber Layer
- 6 S.S Armored Layer

9. Hose construction



- Inner Tube: Black NBR
- 2 Fiber line Layers
- 3 Middle Rubber Layers
- 4 Steel Wire Reinforcement Layers
- 5 Fire-Resistance Rubber Layer
- 6 Green Flame Retardent CR Rubber, Over Rubber Layer NR+CR+SBR of Heat Resistance Fiber.





--Performance Matter, Service Count-----